

VINYL FLOORING PRODUCT CATALOGUE

SERFLOOR.COM.AU

ABOUTUS

Serfloor Australia is a family-owned and operated Flooring and Cladding Systems Manufacturer and Distributor, servicing all states across Australia since 2009. From the beginning, Serfloor Australia paved its way through the flooring market by offering a variety of traditional and industry forward vinyl flooring solutions.

With our passion for innovation, Serfloor soon introduced its wall cladding systems after discovering an unsatisfied demand in the market. This quickly became the ideal solution for both the home renovation, and the architectural and design industry saving time, money and labor with one product.

Our mission is to provide a product portfolio that celebrates the needs of today's urban and contemporary lifestyle without ever compromising on product quality, functionality or service.

> SMART LAY LONGBOARD SMART LAY HERRINGBONE 3MM GLU E DOWN

SMART LAY SHORTBOARD

2MM GLUE DOWN



8|

| 14 |

- | 20 |
- | 34 |
- | 38 |



•

-

1


0



FEATURES

Serfloor's Smart Lay vinyl range is a premium option that features realistic timber look designs and textures but comes with all the benefits of vinyl flooring. Our luxury vinyl plank flooring is designed for easy and fast installation over almost any surface without the need for underlay or expansion gaps.

With two planks sizes available and 22 colours to choose from, the Smartlay range is the perfect alternative to tiles, carpet or engineered timber. Being both soft underfoot and water resistant, it is suitable for almost all residential and commercial spaces.



- Made in South Korea
- Fire, slip, oil & stain resistant
- Reduces impact & sound travel
- Soft and warm under foot
- R10 Slip Rated •

- Durable & low maintenance
- Quick & easy installation
- No adhesive required for residential • applications
- No click system
- Nano-Silver technology .

- Designed for no additional underlay
- Best choice for allergy sufferers
- Authentic wood look with embossed ٠ surface layer
- No expansion gap required
- Dimensionally stable

VINYL AND FIBERGLASS SHEET CORE

The composition of our Smart Lay ensures performance expectations are met, making it a suitable alternative to other flooring options such as engineered timber and laminate.

- Minimal expansion when exposed to temperature changes
- Dimensionally stable compared to timber or fiberglass mesh .
- Easy to cut with a Stanley knife
- Impact resistant
- Virgin material



COMMERCIAL GRADE

With a 0.5 mm wear layer and 15 year commercial wear warranty, you can rest assured that Serfloors luxury vinyl planks are the perfect option for your next commercial project.

- 0.5mm wear layer suitable for heavy commercial use •
- Australian Standard test certificates availabe
- . Supreme durability
- Softer underfoot compared to ceramic tiles or timber floors .
- Easy to keep clean with regular mopping .

PROTECTIVE WEAR LAYER

Serfloor's Smat Lay range is designed to provide longevity with its multilayer structure. Have peace of mind knowing your floor is suitable for everyday use with its scratch and stain resistant surface.


- PU/UV protection •
- Scratch resistant, making Smart Lay suitable for kids and pets
- Reduces maintenance
- 30 years Residential wear warranty
- 15 years Commercial wear warranty .


WATER RESISTANT


The composition of our Smart Lay in combination with our vinyl adhesive makes this product perfect for wet areas.


- Suitable for use in all wet areas including bathroom, kitchen • and laundry
- Easy to clean spills and mess
- Watertight when glued down
- No expansion gap rquired

SMART LAY SHORTBOARD












SERFLOOR.COM.AU


SMART LAY SHORTBOARD













SMART LAY LONGBOARD


















SMART LAY LONGBOARD







SPECIFICATIONS



ECTIVE 30 YEARS RESIDENTIAL WEAR WARRANTY 2 0 15 YEARS COMMERCI ARRAN



Smart Lay Shortboard

Offering 12 versatile wood look colours, Serfloor's Smart Lay shortboard elevates the appearance in any space. With its ideal plank size, these luxury vinyl planks are easy to manage making installation a breeze.



	Smart Lay Shortboard		Smart Lay Longboard	
	STANDARD	RESULT	Standard	Result
Total Thickness (mm)	EN 428	5 mm	EN 428	5 mm
Thickness of Wear Layer (mm)	EN 429	0.5 mm (+/- 0.005)	EN 429	0.5 mm (+/- 0.005)
Weight (+/- 50gr/m2)	EN 430	9.23 kg/m2	EN 430	10.55 kg/m2
Plank Dimension	EN 427	177.8 mm x 1219.2 mm	EN 427	228.6 mm x 1524 mm
Packing	EN 427	10 Planks/2.167 m2 per box	EN 427	7 Planks / 2.44 m2 per box
Acoustic Impact Noise	EN ISO 717-2	IIC = 52	EN ISO 717-2	IIC=52
Dimension Stability	EN 434	< 0.25%	EN 434	< 0.25%
Resistance to Light	ISO 105 B02	>6	ISO 105 B02	>6
Residual Indentation	EN 433	< 0.1 mm	EN 433	< 0.1 mm
Castor Chair Test	ISO 4918	Pass	ISO 4918	Pass
Flexibility	EN 435	Pass	EN 435	Pass
	ASTMD3884	0.1% Loss	ASTMD3884	0.1% Loss
Abrasion Resistance	AS 4586-2013	R10 (>10 <19)	AS 4586-2013	R10 (>10 <19)
Behaviour to Fire	AS/ISO 9239.1-2003	CRF Value: 6.7Kw/M2	AS/ISO 9239.1-2003	CRF Value: 6.7Kw/M2
		Smoke Value: 165%.min		Smoke Value: 165%.min
Chemical Products	ASTMF925	Pass	ASTM F925	Pass
Static Electric Propensity	EN 1815	Voltage: 0.5 kV	EN 1815	Voltage: 0.5 kV
Emission of Formaldehyde	ISO 10580 (<10 (24h) ug.m2.h)	<2.3 (24h) ug.m2.h	ISO 10580 (<10 (24h) ug.m2.h)	<2.3 (24h) ug.m2.h
VOCEmission	ISO 16000	A+	ISO 16000	A+
Wear Resistance	EN 660-2	Wear group: T	EN 660-2	Wear group: T
Surface Treatment	PU/ NANO SILVER	PU & Anti-bacterial, per design	PU/ NANO SILVER	PU & Anti-bacterial, per desig
Adhesive		Recommended		Hard Set adhesive required





Smart Lay Longboard

With 10 realistic wood designs to choose from, Serfloors Smart Lay Longboard range naturally enlarges and enhances the look of any room. Its extra long plank size makes it an ideal choice for larger rooms and open plan spaces.





FEATURES

Smart Lay Herringbone is the all new innovative vinyl flooring solution by Serfloor Australia. An ultimate fusion between the timeless herringbone design pattern, and the well trusted quality of our 5 mm luxury vinyl planks.

Suitable for residential and commercial use, Serfloor's Smart Lay Herringbone can be installed with ease, thanks to its ideal plank size. Transform any space into a luxury area without compromising on comfort or durability.

Offering 9 of the most requested colours from the Serfloor Smart Lay range, it is the perfect alternative to hybrid, laminate or engineered timber floors.



Dimensionally

Stable



Antibacterial

Technology

Water Resistant



Emissions




Scratch and Stain

Resistant





Fade Resistant



Made in South Korea

- Fire, slip, oil & stain resistant
- Reduces impact & sound travel
- Soft and warm under foot
- R10 Slip Rated •

Durable & low maintenance

Quick & easy installation

applications

No click system

.

Nano-Silver technology

- No adhesive required for residential Authentic wood look with embossed ٠ surface layer
 - No expansion gap required

Designed for no additional underlay

Best choice for allergy sufferers

Dimensionally stable •

VINYL AND FIBERGLASS SHEET CORE

The composition of our Smart Lay ensures performance expectations are met, making it a suitable alternative to other flooring options such as engineered timber and laminate.

- Minimal expansion when exposed to temperature changes
- Dimensionally stable compared to timber or fiberglass mesh .
- Easy to cut with a Stanley knife
- Impact resistant
- Virgin material



COMMERCIAL GRADE

With a 0.5 mm wear layer and 15 year commercial wear warranty, you can rest assured that Serfloors luxury vinyl planks are the perfect option for your next commercial project.

- 0.5mm wear layer suitable for heavy commercial use •
- Australian Standard test certificates availabe
- . Supreme durability
- Softer underfoot compared to ceramic tiles or timber floors .
- Easy to keep clean with regular mopping .



PROTECTIVE WEAR LAYER

Serfloor's Smat Lay range is designed to provide longevity with its multilayer structure. Have peace of mind knowing your floor is suitable for everyday use with its scratch and stain resistant surface.

- PU/UV protection
- Scratch resistant, making Smart Lay suitable for kids and pets •
- Reduces maintenance
- 30 years Residential wear warranty
- 15 years Commercial wear warranty

WATER RESISTANT


The composition of our Smart Lay in combination with our vinyl adhesive makes this product perfect for wet areas.

- Suitable for use in all wet areas including bathroom, kitchen • and laundry
- Easy to clean spills and mess
- Watertight when glued down
- No expansion gap rquired

HERRINGBONE


















HERRINGBONE
















HERRINGBONE












SPECIFICATIONS





There are no limits to your imagination when it comes to Smart Lay Herringbone. The individual planks have no restrictions of a click system, allowing them to be laid in endless traditional or modern design variations.

All the colours in the Smart Lay Herringbone collection are also available in standard size straight planks, providing you versality with your projects.



Double Herringbone (refer to pg. 27)

Triple Herringbone (refer to pg. 28 & 29) Square/Diagonal Herringbone (refer to pg. 20, 24, & 28)

	Smart Lay Herringbone		
	STANDARD	RESULT	
Total Thickness (mm)	EN 428	5 mm	
Thickness of Wear Layer (mm)	EN 429	0.5 mm (+/- 0.005)	
Weight (+/- 50gr/m2)	EN 430	10 kg/m2	
Plank Dimension	EN 427	101.6 mm x 457.2 mm	
Packing	EN 427	22 Planks/1.022 m2 per box	
Acoustic Impact Noise	EN ISO 717-2	IIC = 52	
Dimension Stability	EN 434	< 0.25%	
Resistance to Light	ISO 105 B02	>6	
Residual Indentation	EN 433	< 0.1 mm	
Castor Chair Test	ISO 4918	Pass	
Flexibility	EN 435	Pass	
Abrasion Resistance	ASTMD3884	0.1% Loss	
	AS 4586-2013	R10 (>10 <19)	
Behaviour to Fire	AS/ISO 9239.1-2003	CRF Value: 6.7Kw/M2	
		Smoke Value: 165%.min	
Chemical Products	ASTM F925	Pass	
Static Electric Propensity	EN 1815	Voltage: 0.5 kV	
Emission of Formaldehyde	ISO 10580 (<10 (24h) ug.m2.h)	<2.3 (24h) ug.m2.h	
VOC Emission	ISO 16000	A+	
Wear Resistance	EN 660-2	Wear group: T	
Surface Treatment	PU/ NANO SILVER	PU & Anti-bacterial, per design	
Adhesive		Recommended	



GLUE DOWN VINYL PLANKS

Mar 7



3MM VINYL PLANK

Serfloor 3mm Glue Down vinyl planks are a versatile wood look range that can be used for all commercial and domestic environments. With the ability to customise laying patterns, our 3mm vinyl range offers the look and feel of real timber flooring without the higher price point or maintenance requirements.

The planks are 100% water resistant and designed for durability and low maintenance, it is fit for almost any indoor flooring requirement including all wet areas. It is also scratch and stain resistant, making it suitable for busy homes with pets and young children.





· _











Comfortable under Foot

Low VOC Emission Water Resistant

Scratch and Stain Resistant

Antibacterial and Hypoallergenic

Easy to Maintain


•

•

Water resistant Low VOC emissions contribute to

- better indoor air quality UV coated
- Anti-bacterial surface ٠
- Fire, slip, oil & stain resistant •
- 15 years commercial warranty •
- 30 years residential warranty •
- Reduces impact & sound travel •
- Durable & low maintenance •
- Quick & easy installation ٠
- Best choice for allergy sufferers .
- Designed for no underlay •
- Pet and kid friendly •
- Dry-back. Hard set vinyl adhesive required for installation
- Suitable for all wet areas including the bathroom, laundry and kitchen

	Standard	RESULT 3MM
Total Thickness (mm)	EN 428	3.0mm
Thickness of Wear Layer (mm)	EN 429	0.5mm (+/- 0.005)
Weight (+/- 50gr/m2)	EN 430	5.67kg/m2
Plank Dimension	EN 427	184.2mm x 1219.2mm
Packing	EN 427	14 Planks / 3.14m2 per box
Dimension Stability	EN 434	<0.25
Colour Fastness to Light	ISO 105 B02	>6
Residual Indentation	EN 433	> 0.10mm
Acoustic	ISO 717-2:2013	56 dB
Abrasion Resistance	EN 660-2	5.3
Slip Resistance Classification	AS 4586-2013	R10 (>10 <19)
Behaviour to Fire	AS/ISO 9239:1-2003	CRF Value: 8.3Kw/M2
Denaviour to Fire	A3/130 3233.1-2003	Smoke Value: 146%.min
Emission of Formaldehyde	EN 717-2	Not detected
TVOC Emission Factor	ISO 10580	After 24 hours: .22 m2.m3
Chemical Products	ASTM F925	Pass
Electric Behaviour	EN 1081	Pass
Dynamic Coefficient of Friction	ASTM C1028	Direction A: 0.48 / Direction B: 0.58
Surface Treatment	Anti-bacterial	Anti-bacterial, UV protection











UV coating	
o v ooddinig	
0.5mm wear layer	
Photographic film	
3mm vinyl core	
Rubber backing	

















2MM VINYL PLANK

Serfloor 2mm Glue Down vinyl planks are an affordable and elegant option with realistic wood look designs and the choice to customise your laying pattern. It has been designed for easy and fast installation over almost any surface without underlay.

Serfloor glue down flooring is installed with vinyl adhesive which keeps movement in the floor to a minimum when exposed to extreme temperatures, and requires no expansion gaps.



Comfortable under


Foot



 \sim







Scratch and Stain Resistant





Antibacterial and Hypoallergenic


Easy to Maintain


• Water resistant

- Low VOC emissions contribute to . better indoor air quality
- UV coated
- Anti-bacterial surface .
- Fire, slip, oil & stain resistant •
- 15 years commercial warranty .
- 30 years residential warranty •
- Reduces impact & sound travel •
- Durable & low maintenance .
- Quick & easy installation •
- Best choice for allergy sufferers •
- Designed for no underlay ٠
- Pet and kid friendly .
- Dry-back. Hard set vinyl adhesive required for installation
- Suitable for all wet areas including the • bathroom, laundry and kitchen

	Standard	RESULT 2MM
Total Thickness (mm)	EN 428	2.0mm
Thickness of Wear Layer (mm)	EN 429	0.3mm (+/- 0.005)
Weight (+/- 50gr/m2)	EN 430	3.79kg/m2
Plank Dimension	EN 427	184.2mm x 1219.2mm
Packing	EN 427	20 Planks / 4.49m2 per box
Dimension Stability	EN 434	<0.25
Colour Fastness to Light	ISO 105 B02	>6
Residual Indentation	EN 433	> 0.10mm
Acoustic	ISO 717-2:2013	56 dB
Abrasion Resistance	EN 660-2	5.3
Slip Resistance Classification	AS 4586-2013	R10 (>10 <19)
Behaviour to Fire	AS/ISO 92391-2003	CRF Value: 8.3Kw/M2
Denaviour to Fire	A3/130 9239.1-2003	Smoke Value: 146%.min
Emission of Formaldehyde	EN 717-2	Not detected
TVOC Emission Factor	ISO 10580	After 24 hours: .22 m2.m3
Chemical Products	ASTM F925	Pass
Electric Behaviour	EN 1081	Pass
Dynamic Coefficient of Friction	ASTM C1028	Direction A: 0.48 / Direction B: 0.58
Surface Treatment	Anti-bacterial	Anti-bacterial, UV protection

-. ·








Light commercial grade



UV coating	
0 V Coating	
0.3mm wear layer	
Photographic film	
2mm vinyl core	
-	
Rubber backing	















Disclaimer

Serfloor photography and print cannot always produce a perfect representation of our product. This includes the appearance of colour, pattern variation and the presentation of the installation. We strongly recommend you obtain a product sample and view the product in a larger display where possible.



info@serfloor.com.au | (03) 9796 4626 www.serfloor.com.au

Follow us at @serfloor.australia



Back cover: Golden Oak SFG-2202 | Front cover: Blackbutt SFH-6061